

# HDMI-DVI M-M Cable

## USER'S MANUAL

### COPYRIGHT

© 2016. ENEL GROUP OU.

This Manual and information contained in it are copyrighted. All rights reserved. All trademarks are the property of their legal holders.

### NOTICE OF RESPONSIBILITY RESTRICTION

Despite the exerted efforts to make this Manual more exact, some discrepancies may occur. The information of this Manual is given on “as is” terms. The author and the publisher do not bear any liability to a person or an organization for loss or damages, which have arisen from the information contained in the given Manual.

### PURPOSE

The HDMI-DVI M-M cable is designed for connection of a signal source to a TV set or other devices equipped with HDMI and DVI ports.

### FEATURES

- High-Speed HDMI-DVI cable
- HDMI 1.3b – DVI compliant
- Bandwidth capacity: 10.2 Gbps
- Color depth: 48 bit
- HDMI-DVI cable with 28 AWG oxygen-free high purity copper conductors
- Triple shielding protects against interferences

### SAFETY PRECAUTIONS

- Do not use the cable with damaged insulation.
- Do not use in places with possible ingress of liquid, moisture, dust and high temperature exposure.
- The product is beyond repair in case of the cable damage or its connectors.

### TECHNICAL SPECIFICATIONS

Type	HDMI (male 19 pin) – DVI
BitRate, Gbps	up to 10.2
Wire gauge	28 AWG
Wire material	oxygen-free high-purity copper
Cable length, m	1.8

**Note. Technical specifications given in this table are supplemental information and cannot give occasion to claims. TM REAL-EL production is improved constantly, therefore Technical Specifications are subject to change without prior notice.**